







Pathways & Access for Reduced Mobility Persons (RMP)

Pontoons and decking to access beaches, dunes, rivers, lakes and forest paths

- ► Optimized adaptability according to sites configuration
- ► Easy & quick to install
- ► In accordance with the RMP recommendations



Deckings - Stilts - Access ramps

Grooving

DECKING

Panels



Made of treated Douglas fir or heart of Douglas fir, grooved planks 36 mm thick, fixed using stainless steel screws to a wooden backing strip.
Width 2.00 m, length 4.00 m,
Total thickness 110 mm
Delivered assembled
Ref: ME 201

Strips



Made of treated Douglas fir or Heart of Douglas fir, non-slip grooved planks 145 mm x 36 mm en 4.00 m Ref: AM 105 145 mm x 45 mm en 4.00 m Ref: AM 107 145 mm x 80 mm en 4.00 m Ref: AM 109

STILTS



One support every 2.00 m made of two posts 120 x 120 mm,
Non-slip grooved planks to be fixed on joists with stainless steel screws every 0.50 m
Width 2.00 m,
Delivered in kit to install on site
Hardwares provided
Ref: PO 104

ACCESS RAMPS for persons with reduced mobility



Made of treated Douglas fir or Heart of Douglas fir. 5.00 m modular panels, made of non-slip grooved planks 145 x 36 mm, mounted on joists. Passage width 1.50 m Space for the wheels: 80 x 80 mm

Galvanized feet equipped with springs to insure an accurate adjustment to the slope. Rest platforms, length 1.50 m for passage width 1.50 with jacks galvanized feet for an accurate adjustment.

Connection of the different elements with galvanized fishplates

Slopes in accordance with the Access Ramps regulations: in general 4% - except in case of exceptional derogations (4% slopes physically impossible) : 5, 7, 8 and 12% with rest platforms depending on the slopes.

Ref: PMR 201



The decking planks include 8 non-slip grooves and two drop edges.

They are installed with a minimum gap of 5 mm using screws (stainless steel recommended: pre-drilled holes required)

Pressure-treated wood with chromium and arsenic-free preservatives







61160 Villedieu-lès-Bailleul FRANCE

Tel: +33 2 33 36 11 02 Fax: +33 2 33 39 28 75